MOBILE RAMP

TECHNICAL DATA SHEET

AZ-RAMP-WLO-8T-STANDARD-TB

FEATURES

Elevate your loading efficiency with our Heavy-Duty Mobile Loading Ramp, the perfect solution for capacities up to 8 tons. With its compact design and maneuverability, loading and unloading is made effortless. This standard version offers durability and flexibility, ensuring seamless operations. For added protection, the optional tarpaulin tunnel safeguards your goods from the elements. Experience unparalleled ease and safety with our Mobile Loading Ramp. Its robust construction and adjustable design accommo...



REQUEST A QUOTE 🗷

GO TO PRODUCT /

MAKE A SURVEY 🗪

TECHNICAL DATA

| Description | Value |
|---|------------------|
| Static capacity | 8t |
| Maximum length | 10150 mm |
| Full width | 2170 mm |
| Width used | 2000 mm |
| Length of inclined plane | 8800 mm |
| Length of horizontal platform | 1350 mm |
| Length of entry lip | 250 mm |
| Length of exit lip | 0 mm |
| Slopes Min. % - Max. % | 11.25% - 15.56% |
| Adjustable height Min. mm - Max. mm | 900 mm - 1550 mm |
| Unloaded weight | 2400 kg |
| Supports adjustable feet, depending on model. | 2-4 |
| Safety height Side railings | 350 mm - 1200 mm |
| Includes safety chains | 2 |

Features

- Electric lifting of the tilting entry and exit lips (Three-phase 380V-50Hz)
- Dock bumpers with 500 mm refuge area
- Wide ramp, with large horizontal plane at the truck exit
- Intended for use with 3 and 4-wheel forklifts, warehouses, rollers, etc.
- 4 height-adjustable support jacks with adaptable heads
- Anti-slip tread surface of hot-dip galvanized grating
- 35 cm high removable side safety railings
- 2 lashing chains included, ramp on inflatable tires

OPTIONS

| Option | Price |
|----------------------|---------|
| 500mm refuge area | 2 000 € |
| High area railings | 1 000 € |
| Central fork sleeves | 750 € |